

TECHNICAL DATA

TAMPER

BT 60 G, BT 65 G



Work where others stop

Use in deep and narrow trenches and buildings



Practicable

Full power available and filling in just a few minutes



Cost efficient

Economical and commonly available fuel

Shipping dimensions in m3

BT 60 G 0,283


BT 65 G 0,283

Standard Equipment

- ☒ 2 Gas cylinders
- ☒ Filling adapter
- ☒ Engine Protection System
 - Protective engine covering
 - Paper air filter system with two stages
 - Automatic oil level control
- ☒ Vibration insulated steering bow
- ☒ Self-cleaning air filter housing
- ☒ Protective covering
- ☒ Single point lifting device
- ☒ Recoil starter
- ☒ Plastic castor as loading aid
- ☒ Infinitely variable frequency
- ☒ combination of engine and gas switch
- ☒ h-/ rpm meter
- ☒ 3-2-1 Warranty

Optional Equipment

- ☐ Filling station
- ☐ 4 gas cylinders with transport crate
- ☐ Transport device with puncture proof wheels
- ☐ Tamper foot widths (160-330mm)
- ☐ Tamper foot extensions
- ☐ Special painting
- ☐ Tool kit
- ☐ Service Kit
- ☐ TOUGH WARRANTY



Dimensions in mm

	B	H	L	L1	W
BT 60 G	350	1110	728	335	230
BT 65 G	350	1110	728	335	280

Technical Data

Weights

Operating weight CECE	kg
Basic weight	kg

Dimensions

Working width (tamper plate)	mm
------------------------------------	----

Driving Characteristics

Working speed max.	m/min
-------------------------	-------

Drive

Engine manufacturer	
Type	
Cooling	
Number of cylinders	
Performance SAE J 1349	kW
LPG consump. aver. during operation	l/h
Drive system	

Exciter system

Frequency	Hz
Impact force	kN

Capacities

Propane	kg
---------------	----

BOMAG BT 60 G

65
64

230

20

Honda
GXR 120
air
1
2,5
0,4
mech.

10- 11,8
15,0

0,85

BOMAG BT 65 G

75
74

280

20

Honda
GXR 120
air
1
2,5
0,4
mech.

10- 11,8
17,0

0,85

Technical modifications reserved. Machines may be shown with options.

BOMAG
Hellerwald
D-56154 Boppard
P.O. Box 5162
Tel. (0)6742 - 1000
Fax (0)6742 - 3090

